

02/16/99

Please type a plus sign (+) inside this box → ☐PTO/SB/05 (12/97)  
Approved for use through 09/30/00. ONB 0651-0032Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.**UTILITY  
PATENT APPLICATION  
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney docket No. CY-99006

Total Pages 21

First Named Inventor or Application Identifier

Keith R. Barker

Express Mail Label No.

EJ323782799US

**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☒ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 10]  
(preferred arrangement set forth below)  
- Descriptive title of the Invention  
- Cross Reference to Related Applications  
- Statement Regarding Fed sponsored R & D  
- Reference to Microfiche Appendix  
- Background of the Invention  
- Brief Summary of the Invention  
- Brief Description of the Drawings (if filed)  
- Detailed Description  
- Claim(s)  
- Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets 2]
4. Oath of Declaration [Total Pages 2]  
a. ☒ Newly executed (original copy)  
b. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)  
[Note Box 5 below]  
i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath of declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)  
a. ☐ Computer Readable Copy  
b. ☐ Paper Copy (identical to computer copy)  
c. ☐ Statement verifying identity of above copies

**ACCOMPANYING APPLICATION PARTS**

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement  
(when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure  
Statement (IDS)/PTO-1448 ☐ Copies of IDS  
Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application,  
Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
16. ☒ Other: Certificate of Express mailing

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Reissue ☐ Continuation-in-part (CIP) of prior application No. \_\_\_\_\_**18. CORRESPONDENCE ADDRESS**☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

NAME	Joyce E. Kosinski				
ADDRESS	Loral Space and Communications, Ltd. 655 Deep Valley Drive, Suite 303				
CITY	Rolling Hills Estates	STATE	CA	ZIP CODE	90274
COUNTRY	USA	TELEPHONE	(310) 265-9585	FAX	(310) 265-9545

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PATENT  
CY-99006

**RAIN FADE MITIGATION IN A  
DATA TRANSMISSION SYSTEM**

Keith R. Barker  
Mark T. Rafter

## **RAIN FADE MITIGATION IN A DATA TRANSMISSION SYSTEM**

### **BACKGROUND**

The present invention relates generally to data distribution systems and methods, and more particularly, to an improved rain fade mitigation method and data distribution system that distributes data to personal computers.

The assignee of the present invention has developed a satellite-based data distribution system that is used to distribute data from content providers to client personal computers by way of a satellite. This system must reliably operate in the presence of rain.

One currently deployed data broadcasting system, known as the DirecPC™ system developed by Hughes Network Systems, for example, is believed to provide for rain fade mitigation. However, the specifics of the rain fade mitigation is not known. However, such rain fade mitigation is not as critical when transmitting video data. This is because in most cases, the loss of data typically does not result in a complete interruption in transmission. If some data is lost during transmission, the video image may be deteriorated, but the eyes and brain integrate what is displayed making the data loss relatively unnoticeable.

It would be an improvement to have a rain fade mitigation method and one way data distribution system that operates in a rain fade environment. It would also be an improvement to have a rain fade mitigation method and one way satellite-based data distribution system that distributes data to personal computers in a rain fade environment.

## SUMMARY OF THE INVENTION

The present invention provides for a rain fade mitigation method and data distribution system, such as an RF or satellite-based data distribution system, that provides improved performance when the system operates in a rain fade environment. The present invention may be used with any microwave RF transmission system in which rain events degrade or attenuate the communications signal. Typical systems include satellite-based communications, and the like.

In a first embodiment, the system includes a transmitting processor that processes data packets comprising data to be transmitted. A data distribution system is used to transmit the data packets to one or more receivers located at remote locations. The data distribution system is used to transmit the data a first time. The data is then transmitted a second time after a time delay that is nominally equal to the duration of an average rain event. This time is on the order of 20-30 minutes. The receivers receive the data packets and recover the originally transmitted data.

In a second embodiment, the transmitting processor also comprises forward error correction processing software that adds forward error correction bits to data packets containing the data to be transmitted. The data distribution system is used to transmit the data packets to one or more receivers located at remote locations. The packets are transmitted two or more times with a time delay between transmissions that is nominally equal to the duration of an average rain event. The receivers receive the transmitted packets, and also comprise forward error correction software that processes the received data packets to reconstruct the original data. The number of forward error correction bits added to each packet is configurable, and is typically up to about fifty percent of the number of bits in the data packet.

In a third embodiment, the data packets include forward error correction bits and are transmitted one time at a relatively slow transmission rate. The data transmission rate is chosen so that the time required to transmit the data to the receiver is greater than or equal to the time necessary to transmit the data plus the amount of time equal to an average rain fade event (20-30 minutes).

The approaches implement by the present invention provide for more efficient overall data transfer and the ability to transfer large data files more efficiently than previous systems. The use of additional forward error correction bits (overhead) in the data packets transmitted to the client personal computers also allows the system to have a reduced bandwidth and reduced data transmission rate.

The present invention may add up to fifty percent additional overhead to the data packets. This allows the loss of fifty percent of the data while still allowing the data to

be recovered at the client personal computers. This technique ensures reception of the transmitted data in a rain fade environment.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The various features and advantages of the present invention may be more readily understood with reference to the following detailed description taken in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements, and in which:

Fig. 1 illustrates an exemplary satellite-based data broadcasting system for distributing data to personal computers;

Fig. 2 illustrates a first exemplary embodiment of a rain fade mitigation method in accordance with the principles of the present invention;

Fig. 3 illustrates a second exemplary embodiment of a rain fade mitigation method in accordance with the principles of the present invention; and

Fig. 4 illustrates a third exemplary embodiment of a rain fade mitigation method in accordance with the principles of the present invention.

### **DETAILED DESCRIPTION**

Referring to the drawing figures, Fig. 1 illustrates an exemplary satellite-based data broadcasting system 10 in which rain fade mitigation methods 30 (Figs. 2-4) in accordance with the principles of the present invention may be employed. The system 10 is designed to distribute data derived from a transmitting processor 11 by way of a data distribution system 20 to one or more client personal computers 15 (or server computers 15) that are remotely located from the transmitting processor 11. The data distribution system 20 may comprise an RF or satellite-based data distribution system, for example. Fig. 1 illustrates a typical satellite-based data distribution system employing a satellite 13.

The transmitting processor 11 may include forward error correction (FEC) processing software that is used to add forward error correction bits to data packets containing data to be transmitted. The data distribution system 20 comprises a transmitter 12 that is part of or coupled to the transmitting processor 11 and that is used to transmit, or uplink, the packets containing the data (and forward error correction bits) to the satellite 13. The satellite 13 retransmits, or downlinks, the data packets to one or more receivers 14 that are respectively coupled to or are contained in one or more client personal computers 15. When error correction bits are added to the data prior to transmission, the receivers 14 or client personal computers 15 include forward error

correction software that processes the received data packets to reconstruct the original data.

Details of the various systems 10 and methods 30 of the present invention will be described in more detail with reference to Figs. 2-4. Fig. 2 illustrates a first exemplary embodiment of a rain fade mitigation method 30 in accordance with the principles of the present invention. The first exemplary rain fade mitigation method 30 comprises the following steps and is implemented in the system 10 as follows.

In the first embodiment of the method 30 and system 10, the transmitting processor 11 processes the data to form 31 data packets containing data to be transmitted. The data distribution system 20 is used to transmit 32 the data packets a first time to one or more receivers 14 that are respectively coupled to or are contained in one or more client personal computers 15 (server computers 15) located at remote locations. The receivers 14 receive 33 the transmitted data packets. The data distribution system 20 is used to transmit 34 the data packets a second time after a time delay having a specified duration that is related to a rain fade event and which is sufficient to allow data reconstruction in the presence of the rain fade event. The average time delay is typically on the order of 20-30 minutes. The delay is adjusted to account for local rain conditions. The receivers 14 receive 35 the data packets that were transmitted the second time. The receivers 14 or client personal computers 15 process the data packets transmitted both times to recover or reconstruct 36 the originally transmitted data.

In a second embodiment of the system 10 and method 30 illustrated with reference to Figs. 1 and 3, the transmitting processor 11 processes the data to form 31 data packets containing data to be transmitted and further comprises forward error correction processing software that adds forward error correction bits to the data packets that are to be transmitted. The data distribution system transmits 32 the data packets a first time to one or more receivers 14 that are respectively coupled to or are contained in one or more client personal computers 15 located at the remote locations. The data packets containing the data and forward error correction bits are transmitted 32, 34 a second time after a time delay having a duration that is related to a rain fade event and which is sufficient to allow data reconstruction in the presence of the rain fade event. The delay is adjusted for local rain conditions. The receivers 14 receive 33, 35 the transmitted packets, and the receivers 14 or client personal computers 15 also comprise forward error correction software that processes the received data packets to reconstruct 36 the original data. The number of forward error correction bits added to each packet is configurable, and is typically up to about fifty percent of the number of bits in the data packet.

In a third embodiment of the system 10 and method 30 illustrated with reference to Figs. 1 and 4, the transmitting processor 11 processes the data to form 31 data packets containing data to be transmitted and further comprises forward error correction processing software that adds forward error correction bits to the data packets that are to be transmitted. The data packets are transmitted 32 one time at a relatively slow transmission rate. The data transmission rate is chosen so that the time required to transmit the data to the one or more receivers 14 or client personal computers 15 is greater than or equal to the time necessary to transmit the data plus the amount of time having a duration that is related to a rain fade event and which is sufficient to allow data reconstruction in the presence of the rain fade event. The time delay corresponding to an typical rain fade event in many parts of the United States is on the order of 20-30 minutes. Of course, the delay is adjusted for local rain conditions. The receivers 14 receives 33 the transmitted packets, and forward error correction software contained in the receivers 14 or client personal computers 15 processes the received data packets to reconstruct 36 the original data.

Typically, the additional forward error correction bits that are added to the data packets are on the order of fifty percent of the data bits in each packet. However, it is to be understood that the overhead provided by the additional forward error correction bits is configurable depending upon the application and the amount of rain fade mitigation that is required.

Assuming, for example, that fifty percent overhead is added to the data packets, and one third of the data in each packet comprises forward error correction bits, up to fifty percent of the transmitted data may be lost due to the effects of rain, and the original data may still be reconstructed. If the data is transmitted over a one hour period and a rain storm lasts 20 minutes, all of the original data may be reconstructed. The present invention thus ensures reception of the transmitted data in a rain fade environment.

Thus, rain fade mitigation systems and methods for use in data distribution systems have been disclosed. It is to be understood that the described embodiments are merely illustrative of some of the many specific embodiments that represent applications of the principles of the present invention. Clearly, numerous and other arrangements can be readily devised by those skilled in the art without departing from the scope of the invention.

## CLAIMS

What is claimed is:

1. A data broadcasting system for distributing data to one or more remote locations in a rain fade environment, comprising:
  - a transmitting processor for forming data packets comprising data to be transmitted;
  - a data distribution system for transmitting the data packets at least two times to one or more receivers located at remote locations, which times are separated by a time delay having a duration that is related to a rain fade event, which time delay is sufficient to allow data reconstruction in the presence of the rain fade event; and
  - the one or more receivers receiving the data packets and processing the data packets transmitted the at least two times to reconstruct the originally transmitted data.
2. The system recited in Claim 1 wherein the data broadcast system comprises a satellite.
3. The system recited in Claim 1 wherein the data broadcast system comprises an RF data broadcast system.
4. The system recited in Claim 1 wherein the data packets contain data to be transmitted and forward error correction bits.
5. The system recited in Claim 4 wherein the data broadcast system comprises a satellite.
6. The system recited in Claim 4 wherein the data broadcast system comprises an RF data broadcast system.
7. The system recited in Claim 4 wherein the number of forward error correction bits added to each packet is configurable.
8. A data broadcast system for distributing data to one or more remote locations in a rain fade environment, comprising:
  - a transmitting processor for forming data packets comprising data to be transmitted and forward error correction bits;



the receivers receiving the data packets and processing the received data packets using forward error correction processing to reconstruct the original data.

9. The system recited in Claim 8 wherein the data broadcast system comprises a satellite.

10. The system recited in Claim 8 wherein the data broadcast system comprises an RF data broadcast system.

11. The system recited in Claim 8 wherein the number of forward error correction bits added to each packet is configurable.

13. A rain fade mitigation method for distributing data to one or more remote locations in a rain fade environment, comprising the steps of:

forming data packets comprising data to be transmitted;

transmitting the data packets at least two times to one or more remote locations, which times are separated by a time delay having a duration that is related to a rain fade event, which time delay is sufficient to allow data reconstruction in the presence of the rain fade event;

receiving the data packets at the one or more remote locations; and

processing the received data packets at the one or more remote locations to reconstruct the data.

14. The method recited in Claim 13 wherein the number of forward error correction bits added to each packet is configurable.

15. The method recited in Claim 13 wherein:

the step of forming data packets comprises the step of forming data packets containing data to be transmitted and forward error correction bits;

the step of transmitting the data packets comprises the step of transmitting the data packets and forward error correction bits at least two times to one or more remote locations;

the step of receiving the data packets comprises the step of receiving the data packets and forward error correction bits at the one or more remote locations; and

the step of processing the received data packets comprises the step of forward error correction processing the received data packets and forward error correction bits at the one or more remote locations to reconstruct the original data.

16. The method recited in Claim 15 wherein the number of forward error correction bits added to each packet is configurable.

17. A rain fade mitigation method for distributing data to one or more remote locations in a rain fade environment, comprising the steps of:

forming data packets comprising data to be transmitted and forward error correction bits;

transmitting the data packets and forward error correction bits to one or more remote locations, which data packets are transmitted at a relatively slow transmission rate such that the time required to transmit the data to the one or more receivers is greater than or equal to the time necessary to transmit the data plus an amount of time sufficient to allow data reconstruction in the presence of a rain fade event;

receiving the data packets and forward error correction bits at the one or more remote locations; and

forward error correction processing the received data packets and forward error correction bits to reconstruct the original data.

18. The method recited in Claim 17 wherein the number of forward error correction bits added to each packet is configurable.

## **RAIN FADE MITIGATION IN A DATA TRANSMISSION SYSTEM**

### **ABSTRACT**

Rain fade mitigation methods and data broadcast systems that provide improved performance in a rain fade environment. The systems distribute data derived from a transmitting processor by way of a data distribution system to one or more receivers located at remote locations. The transmitting processor may include forward error correction processing software that is used to add forward error correction bits to data packets to be transmitted. When error correction bits are added to the data prior to transmission, the receivers include forward error correction software that processes the received data packets to reconstruct the original data. Data packets with or without error correcting bits may be transmitted two times to the remote locations, which times are separated by a time delay having a duration that is related to a rain fade event, which time delay is sufficient to allow data reconstruction in the presence of the rain fade event. The data packets may also be transmitted to the remote locations at a relatively slow transmission rate such that the time required to transmit the data to the one or more remote locations is greater than or equal to the time necessary to transmit the data plus the amount of time equal to an average rain fade event. The data packets are received at the remote locations and appropriately processed to reconstruct the original data.




Fig. 1




Fig. 2




Fig. 3





Fig. 4



**COMBINED DECLARATION FOR PATENT APPLICATION  
AND POWER OF ATTORNEY**

Page 1  
PD- CY-99006

- ☒ Original  
☐ Continuation  
☐ Division  
☐ Continuation-in-part  
☐ Supplemental  
☐ PCT  
☐ Design

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled Rain Fade Mitigation in a Data Transmission System

the specification of which

(check one) ☒ is attached hereto  
☐ was filed on \_\_\_\_\_ as \_\_\_\_\_ Application Serial No. \_\_\_\_\_ and (a) [other than supplemental] was amended on or (b) [supplemental] with amendments through \_\_\_\_\_

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of the application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Priority Claimed

☐  
Yes

☐  
No

\_\_\_\_\_  
Number

\_\_\_\_\_  
Country

\_\_\_\_\_  
Day/Month/Year filed

I hereby claim the benefit under Title 35, United States Code, §120 of any United States applications(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

\_\_\_\_\_  
Application Serial No.

\_\_\_\_\_  
Filing Date

\_\_\_\_\_  
Status  
(patented, pending, abandoned)

## DECLARATION

Page 2

PD- CY-99006



I hereby appoint the following attorneys, or agent and attorneys, to prosecute the application and to transact all business in the Patent and Trademark Office connected therewith:

Kenneth W. Float, Registration No. 29,233

Anthony W. Karambelas Registration No. 25,657

Address telephone calls to Kenneth W. Float at (949) 459-5519. Address correspondence to Joyce Kosinski, Patent Administrator, Loral Space and Communications, 655 Deep Valley Drive, Suite 303, Rolling Hills Estates, CA 90274.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST JOINT INVENTOR Keith R. Barker	INVENTOR'S SIGNATURE 	DATE 2/10/99
RESIDENCE 2707 Hallmark Drive Belmont CA 94002		CITIZENSHIP U.S.A.
POST OFFICE ADDRESS 2707 Hallmark Drive, Belmont, CA 94002		
FULL NAME OF JOINT INVENTOR Mark T. Rafter	INVENTOR'S SIGNATURE 	DATE 10 Feb-99
RESIDENCE 23750 Oak Flat Road Los Gatos CA 95033		CITIZENSHIP U.S.A.
POST OFFICE ADDRESS 23750 Oak Flat Road, Los Gatos, CA 95033		
FULL NAME OF JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF JOINT INVENTOR	INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		

655 DEEP VALLEY DRIVE  
ROLLING HILLS ESTATES  
CA 90274